

APPLICATION FOR CURB CUT PERMIT

ADDRESS OF CUT: _____

NAME: _____ ADDRESS: _____

PHONE: _____

LOT SIZE: _____

MATERIAL: CONCRETE ASPHALT

CONTRACTOR'S NAME: _____

DIRECTOR OF PUBLIC WORKS

CURB CUTS

4.15 **CURB CUTS**, NO OPENING IN OR THROUGH ANY CURB OF ANY STREET SHALL BE MADE WITHOUT FIRST OBTAINING A WRITTEN PERMIT FROM THE SUPERINTENDENT. CURB CUTS AND SIDEWALK DRIVEWAY CROSSINGS TO PROVIDE ACCESS TO PRIVATE PROPERTY SHALL COMPLY WITH THE FOLLOWING:

- (1) NO SINGLE CURB CUT SHALL EXCEED TWENTY-FIVE (25) FEET AND SHALL NOT BE LESS THAN TEN (10) FEET AT THE STREET LINE OR LESS THAN EIGHT (8) FEET AT THE OUTSIDE SIDEWALK LINE.
- (2) THE MINIMUM DISTANCE BETWEEN ANY CURB CUT AND A PUBLIC CROSSWALK SHALL BE FIVE (5) FEET.
- (3) THE MINIMUM DISTANCE BETWEEN CURB CUTS, EXCEPT THOSE SERVING RESIDENTIAL PROPERTIES, SHALL BE TWENTY-FIVE (25) FEET.
- (4) THE MAXIMUM NUMBER OF LINEAL FEET OF SIDEWALK DRIVEWAY CROSSING PERMITTED FOR ANY LOT, PARCEL OF LAND, BUSINESS OR ENTERPRISE, SHALL BE FORTY-FIVE PERCENT (45%) OF THE TOTAL ABUTTING STREET FRONTAGE UP TO AN INCLUDING TWO HUNDRED (200) LINEAL FEET OF STREET FRONTAGE IN EXCESS OF TWO HUNDRED (200) FEET
- (5) THE NECESSARY ADJUSTMENTS TO UTILITY POLES, LIGHT STANDARDS, FIRE HYDRANTS, CATCH BASINS, STREET OF RAIL WAY SIGNS, SIGNALS, OR OTHER PUBLIC IMPROVEMENTS OR INSTALLATIONS SHALL BE ACCOMPLISHED WITHOUT COST TO THE CITY.
- (6) DRIVEWAYS OVER SIDEWALK LINES SHALL BE OF CONCRETE AT LEAST SIX INCHES (6") THICK. DRIVEWAY APRONS, BETWEEN THE SIDEWALK AND THE STREET, SHALL BE OF CONCRETE SIX INCHES (6") THICK.